

NDAA
Compliant



Content

Who are We?	3
About NDAA	4
Introducing NDAA	5
What is DORI	6
What is EYENOR	8
Eyenor CAMERAS	10
Eyenor RECORDERS	16
Eyenor ACCESSORIES	22
Eyenor SOFTWARE	26
Norden Partner Program	28
Talk to US	32

Who are WE?

Norden is a global brand that brings together excellence with international standards. It proudly incorporates sub-brands that have innovative and excellent products.

Eyenor, a sub-brand of Norden, specialises in IP Video Surveillance. It is dedicated to bringing the best and comprehensive range of IP cameras that suit the surveillance need of the evolving market.

Eyenor, being a leading brand of security solutions with the most innovative technology, aims to simplify the safety concerns of the market.

MEETS ALL THE STANDARDS OF OUR CLIENTS IN THE UK & EUROPE

KNOW MORE

Eyenor has its focus adhered to the aspirations and needs of customers. While keeping them in mind, Eyenor brings high-performance surveillance products to the market, which is in demand. We offer a comprehensive range of IP cameras that suits the surveillance & security demands of the evolving market. We continuously strive for excellence in all aspects of our business by integrating sustainable development and innovation.



GLOBAL NAME



**AVANT- GARDE
FEATURES**



**OUTSTANDING SUPPORT
AND SERVICE PROVIDER**

About NDAA

The National Defence Authorisation of the NDAA is a set of US federal laws which stipulate the yearly budget and expenditure of the Defence Department of the United States.

The new order of the John McCain National Defence Authorisation Act restrains the use, procurement, or sale of surveillance solutions belonging to certain brands to the federal bureaus. In the same token, these agencies are also banned from buying equipment and conducting businesses with restricted companies. During such cases, the federal structures face challenges approving the dependable brands as manufacturing takes place in many countries.

NDA Compliant



What is DORI

WHAT IS DORI & HOW TO USE IN CCTV DESIGN

In the world of CCTV, DORI stands for Detection, Observation, Recognition and Identification.

DETECTION

The detection level allows for reliable and easy determination of whether a person or vehicle is present.

OBSERVATION

The observation level gives characteristic details of an individual, such as distinctive clothing, while allowing a view of activity surrounding an incident.

RECOGNITION

The recognition level determines with a high degree of certainty whether an individual shown is the same as someone that has seen before.

IDENTITY

The identification level enables the identity of an individual beyond a reasonable

DORI

WHAT IS THE DORI STANDARD SYSTEM?

The DORI standard system (based on the IEC EN62676-4:2015 International Standard) defines different levels of detail for

- Detection (25PPM)
- Observation (62 PPM)
- Recognition (125PPM), and
- Identification (250PPM)

For visible light surveillance cameras.

By using these PPM values, it is possible to rate cameras by sensor/lens combination and verify that it will provide the performance needed in each application.



Eyenor Professional SERIES

The Eyenor Professional Series of IP Cameras and Recorders for solutions demand the best in Video Surveillance and Recording across many industries and verticals, including hospitals, malls, banks, institutions, etc. They come with interesting features like Trip Wire, Motion Security, Intrusion Detection, etc.

PRESENTING EYENOR

We are a leading global manufacturer of IP video surveillance solutions. Eyenor cameras and solutions are addressing the needs of multiple sectors. Its cameras and solutions cater to multiple folds of the sector, including malls, buildings, educational institutes, commercial institutes, city surveillance and industries.



2MP FIXED COMPACT BULLET CAMERA

Model No.	ENC-HCB5F-30R-15
Appearance	
Type	2MP STARLIGHT IR IP H.265 FIXED BULLET CAMERA
Image Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS
Lens Type	Fixed
Focal length	2.8/4mm
Detection distance	43.4 m (2.8mm Lens), 62.1 m (4mm Lens)
Observation Distance	43.4 m (2.8mm Lens), 62.1 m (4mm Lens)
Recognition Distance	8.7 m (2.8mm Lens), 12.4 m (4mm Lens)
Identification Distance	4.3 m (2.8 mm Lens), 6.2 m (4mm Lens)
Minimum Illumination	Colour: 0.002Lux (F1.8, AGC ON); B/W: 0Lux with IR
Smart IR	Up to 30m
Smart Defog	Digital Defog
WDR	120dB
Video Compression	H.265+, H.265, H.264, MJPEG
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Behavior Detection	Intrusion, Crossing line
Statistical Analysis	Motion detection, Tampering alarm, Audio detection
Edge Storage	Built in Micro Sd Card Slot upto 128GB support
Audio I/O	N/A
Alarm I/O	N/A
Built-in Mic	Supported
Built-in Speaker	Supported
Ingress Protection	IP67
Vandal Resistant	N/A
Reset Button	N/A
Dimensions (Ø x H)	191x75x74mm
Weight	0.41 Kg

2MP PTZ DOME CAMERA

Model No.	ENC-HHP5Z-250R-14
Appearance	
Type	2MP PTZ DOME CAMERA
Image Sensor	1/1.8", CMOS Progressive 2.0 MegaPixel
Lens Type	5.7 ~ 256.5mm, AF automatic focusing and motorized zoom lens
Focal Length	
Detection distance	76.6 m (5.7 mm Lens), 3330.6 m (256.5 mm Lens)
Observation Distance	30.6 m (5.7 mm Lens), 1332.2 m (256.5 mm Lens)
Recognition Distance	15.3 m (5.7 mm Lens), 666.1 m (256.5 mm Lens)
Identification Distance	7.6 m (5.7 mm Lens), 333.1 m (256.5 mm Lens)
Minimum Illumination	Colour: 0.0005 lux F1.3; 0 lux with IR
Smart IR	Up to 250 m
Smart Defog	Digital & Optical Defog
WDR	120dB
Video Compression	H.265+, H.265, H.264, MJPEG
OSD	Up to 8 OSDs
Privacy Mask	Up to 24 areas
ROI	Up to 8 areas
Motion Detection	Supported
Behavior Detection	N/A
Statistical Analysis	N/A
Edge Storage	Micro SD, up to 256GB
Audio I/O	1/1
Alarm I/O	7/2
Built-in Mic	N/A
Built-in Speaker	N/A
Ingress Protection	IP66
Vandal Resistant	N/A
Reset Button	Supported
Dimensions (Ø x H)	Ø270 x 497 mm
Weight	10.3 Kg

4MP FIXED DOME CAMERA

Model No.	ENV-HD07F-30R-15
Appearance	
Type	4MP FIXED DOME CAMERA
Image Sensor	1/3" CMOS Progressive 4.0 MegaPixel
Lens Type	Fixed
Focal Length	2.8mm / 4mm
Detection distance	63 m(2.8mm Lens), 90 m(4mm Lens)
Observation Distance	25.2 m(2.8 mm Lens), 36 (4mm Lens)
Recognition Distance	12.6 m(2.8 mm Lens), 18 (4mm Lens)
Identification Distance	6.3 m(2.8 mm Lens), 9 m(4mm Lens)
Minimum Illumination	Colour: 0.005 lux @ F1.6, B/W: 0 lux with IR
Smart IR	Up to 30 m
Smart Defog	Smart Defog
WDR	120dB
Video Compression	H.265+, H.265, H.264, MJPEG
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 regions
ROI	Up to 4 areas
Motion Detection	Up to 4 areas
Behavior Detection	Human Body Detection
Statistical Analysis	Motion detection, Tampering alarm
Edge Storage	MicroSD card slot, up to 256 GB
Audio I/O	N/A
Alarm I/O	N/A
Built-in Mic	N/A
Built-in Speaker	N/A
Ingress Protection	IP67
Vandal Resistant	N/A
Reset Button	Supported
Dimensions (mm)	Ø118 x 96 mm
Weight	0.35 Kg

4MP MOTORIZED VANDAL DOME CAMERA

Model No.	ENV-HVD7M-40R-15
Appearance	
Type	4MP MOTORIZED VANDAL DOME CAMERA
Image Sensor	1/3", CMOS Progressive 4.0 MegaPixel
Lens Type	2.8 - 12mm, AF automatic focusing and motorized zoom lens
Detection distance	42 m(2.8mm Lens), 180 m(12mm Lens)
Observation Distance	16.8 m(2.8mm Lens), 72 (12mm Lens)
Recognition Distance	8.4 m(2.8mm Lens), 36 m(12mm Lens)
Identification Distance	4.2 m(2.8 mm Lens), 18 m(12mm Lens)
Minimum Illumination	Colour: 0.003 lux F1.6, 0 lux with IR
Smart IR	Up to 40 m
Smart Defog	Smart Defog
WDR	120dB
Video Compression	H.265+, H.265, H.264, MJPEG
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 regions
ROI	Up to 4 areas
Motion Detection	Up to 4 areas
Behavior Detection	Cross line, intrusion(based on human body detection), motion detection, tampering alarm, audio detection
Statistical Analysis	N/A
Edge Storage	Micro SD, up to 256 GB
Audio I/O	N/A
Alarm I/O	N/A
Built-in Mic	Supported
Ingress Protection	IP67
Vandal Resistant	IK10
Reset Button	Supported
Dimensions (Ø x H)	Ø128x100 mm
Weight	0.65 kg

5MP COMPACT FIXED DOME CAMERA

Model No.	ENC-HCD8F-00R-15
Appearance	
Type	5MP COMPACT FIXED DOME CAMERA
Image Sensor	1/2.7" CMOS Progressive 5.0 MegaPixel
Lens Type	Fixed
Focal length	N/A
Detection distance	63.0 m (2.8mm Lens), 90.0 m (4mm Lens)
Observation Distance	12.6 m (2.8mm Lens), 18.0 m (4mm Lens)
Recognition Distance	12.6 m (2.8mm Lens), 18.0 m (4mm Lens)
Identification Distance	6.3 m (2.8 mm Lens), 9.0 m (4mm Lens)
Minimum Illumination	Color: 0.001 lux @ F1.0, B/W: 0 lux with IR
Smart IR	Up to 30 m
Smart Defog	Smart Defog
WDR	120 dB
Video Compression	H.265+, H.265, H.264, MJPEG
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 regions
ROI	Up to 8 areas
Motion Detection	N/A
Behavior Detection	N/A
Statistical Analysis	Tampering alarm, Motion detection, Audio detection
Edge Storage	Built-in MicroSD card slot, up to 256 GB
Audio I/O	N/A
Alarm I/O	N/A
Built-in Mic	Supported
Built-in Speaker	N/A
Ingress Protection	IP67
Vandal Resistant	N/A
Reset Button	N/A
Dimensions (Ø x H)	Ø110.5 x 94.1 mm
Weight	0.44 Kg

5MP FIXED VANDAL DOME CAMERA

Model No.	ENC-HVD8F-30R-20
Appearance	
Type	5MP FIXED VANDAL DOME CAMERA
Image Sensor	1/2.7", CMOS Progressive 5.0 MegaPixel
Lens Type	2.8 / 4.0mm
Focal length	N/A
Detection distance	63.0 m (2.8mm Lens), 90.0 m (4mm Lens)
Observation Distance	25.2 m (2.8 mm Lens), 36.0 (4mm Lens)
Recognition Distance	12.6 m (2.8mm Lens), 18.0 m (4mm Lens)
Identification Distance	6.3 m (2.8 mm Lens), 9.0 m (4mm Lens)
Minimum Illumination	Colour: 0.003 lux F1.6, 0 lux with IR
Smart IR	Up to 30 m
Smart Defog	Smart Defog
WDR	120dB
Video Compression	H.265+, H.265, H.264, MJPEG
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Behaviour Detection	N/A
Statistical Analysis	Motion detection, Tampering alarm, Audio Detection
Edge Storage	Micro SD, up to 256 GB
Audio I/O	1/1
Alarm I/O	1/1
Built-in Mic	N/A
Built-in Speaker	N/A
Ingress Protection	IP67
Vandal Resistant	IK10
Reset Button	N/A
Dimensions (Ø x H)	Ø108.7 x 81.1 mm
Weight	0.42 kg

5MP FISHEYE FIXED DOME CAMERA

Model No.	ENV-HVD8H-10R-17
Appearance	
Type	5MP FISHEYE FIXED DOME CAMERA
Image Sensor	1/2.8", CMOS Progressive 5.0 MegaPixel
Lens Type	Fixed
Focal length	1.4 mm
Detection distance	31.5 m
Observation Distance	12.6 m
Recognition Distance	8.3 m
Identification Distance	3.2 m
Minimum Illumination	Colour: 0.01 lux @ F2.0; B/W: 0 lux with IR
Smart IR	Up to 10 m
Smart Defog	Smart Defog
WDR	120 dB
Video Compression	H.265+, H.265, H.264, MJPEG
OSD	Up to 8 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Behavior Detection	N/A
Statistical Analysis	N/A
Edge Storage	Micro SD, up to 256GB
Audio I/O	I/I
Alarm I/O	I/I
Built-in Mic	Supported (2 Nos)
Built-in Speaker	N/A
Ingress Protection	IP66
Vandal Resistant	IK10
Reset Button	Supported
Dimensions (Ø x H)	Ø125 * 44 mm
Weight	0.38 kg

5MP PTZ DOME CAMERA

Model No.	ENC-HHP8Z-50R-11
Appearance	
Type	5MP PTZ DOME CAMERA
Image Sensor	1/2.7" CMOS Progressive 5.0 MegaPixel
Lens Type	2.8-12 mm, AF automatic focusing and motorized zoom lens
Focal Length	N/A
Detection distance	63.0 m (2.8 mm Lens), 270.0 m (12 mm Lens)
Observation Distance	25.2 m (2.8 mm Lens), 108.0 m (12 mm Lens)
Recognition Distance	12.6 m (2.8 mm Lens), 54.0 m (12 mm Lens)
Identification Distance	6.3 m (2.8 mm Lens), 27.0 m (12 mm Lens)
Minimum Illumination	Colour: 0.003 lux @ F1.6, 0 lux with IR
Smart IR	Up to 50 m
Smart Defog	Smart Defog
WDR	N/A
Video Compression	H.265+, H.265, H.264, MJPEG
OSD	Upto 8 OSDs
Privacy Mask	Up to 8 areas
ROI	Up to 8 areas
Motion Detection	Up to 4 areas
Behaviour Detection	N/A
Statistical Analysis	Motion detection, Tampering alarm, Audio Detection
Edge Storage	Micro SD, up to 256 GB
Audio I/O	N/A
Alarm I/O	N/A
Built-in Mic	N/A
Ingress Protection	IP66
Vandal Resistant	IK10
Reset Button	Supported
Dimensions (Ø x H)	Ø133*269.4 mm
Weight	0.87 kg

8MP FIXED COMPACT DOME CAMERA

Model No.	ENV-HDQAF-30R-12
Appearance	
Type	8MP FIXED COMPACT DOME CAMERA
Image Sensor	1/3", CMOS Progressive 8.0 MegaPixel
Lens Type	2.8 / 4.0 mm
Focal Length	N/A
Detection distance	84.0 m (2.8 mm Lens), 120.0 m (4.0 mm Lens)
Observation Distance	33.6 m (2.8 mm Lens), 48.0 m (4.0 mm Lens)
Recognition Distance	16.8 m (2.8 mm Lens), 24.0 m (4.0 mm Lens)
Identification Distance	8.4 m (2.8 mm Lens), 12.0 m (4.0 mm Lens)
Minimum Illumination	Colour: 0.05 lux @ F2.0, 0 lux with IR
Smart IR	Up to 30 m
Smart Defog	Smart Defog
WDR	120dB
Video Compression	H.265+, H.265, H.264, MJPEG
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
Behavior Detection	Intrusion, Human Body Detection, Motion detection, Tampering alarm
Statistical Analysis	N/A
Edge Storage	N/A
Audio I/O	N/A
Alarm I/O	N/A
Built-in Mic	N/A
Ingress Protection	IP67
Vandal Resistant	N/A
Reset Button	N/A
Dimensions (Ø x H)	Ø118 x 96 mm
Weight	0.33 kg

8MP MOTORIZED VANDAL DOME CAMERA

Model No.	ENC-HCVAM-40R-15
Appearance	
Type	8MP MOTORIZED VANDAL DOME CAMERA
Image Sensor	1/2.8", 8.0 megapixel, progressive scan, CMOS
Lens Type	2.8 - 12mm, AF automatic focusing and motorized zoom lens
Focal Length	N/A
Detection distance	86.9 m (2.8 mm Lens), 372.4 m (12 mm Lens)
Observation Distance	34.8 m (2.8 mm Lens), 149.0 m (12 mm Lens)
Recognition Distance	17.4 m (2.8 mm Lens), 74.5 m (12 mm Lens)
Identification Distance	8.7m (2.8 mm Lens), 37.2 m (12 mm Lens)
Minimum Illumination	Colour: 0.003 lux @ F1.6, 0 lux with IR
Smart IR	Up to 40 m
Smart Defog	Smart Defog
WDR	120dB
Video Compression	H.265+, H.265, H.264, MJPEG
OSD	Upto 80 SDs
Privacy Mask	Up to 4 areas
ROI	Up to 8 areas
Motion Detection	Supported
Behavior Detection	N/A
Statistical Analysis	Motion detection, tampering alarm, audio detection
Edge Storage	Micro SD, up to 256 GB
Audio I/O	N/A
Alarm I/O	N/A
Built-in Mic	Supported
Built-in Speaker	N/A
Ingress Protection	IP67
Vandal Resistant	IK10
Reset Button	Supported
Dimensions (Ø x H)	Ø129 x 110 mm
Weight	0.69kg

8MP FIXED COMPACT BULLET CAMERA

Model No.	ENV-HCBAF-30R-12
Appearance	
Type	8MP FIXED COMPACT BULLET CAMERA
Image Sensor	1/3", CMOS Progressive 8.0 MegaPixel
Lens Type	2.8 / 4.0 mm
Focal length	N/A
Detection distance	84 m (2.8 mm Lens), 120 m (4 mm Lens)
Observation Distance	33.6 m (2.8 mm Lens), 48 m (4 mm Lens)
Recognition Distance	16.8 m (2.8 mm Lens), 24 m (4 mm Lens)
Identification Distance	8.4 m (2.8 mm Lens), 12 m (4 mm Lens)
Minimum Illumination	Colour: 0.05 lux @ F2.0, 0 lux with IR
Smart IR	Up to 30 m
Smart Defog	Smart Defog
WDR	120dB
Video Compression	H.265+, H.265, H.264, MJPEG
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
behaviour Detection	Intrusion, Human Body Detection, Motion Detection, Tampering alarm
Statistical Analysis	N/A
Edge Storage	N/A
Audio I/O	N/A
Alarm I/O	N/A
Built-in Mic	N/A
Built-in Speaker	N/A
Ingress Protection	IP67
Vandal Resistant	N/A
Reset Button	Supported
Dimensions (L × W × H)	167.3×62.9×62.7 mm
Weight	0.45 kg

Network Video RECORDERS

Eyenor Network Video Recorders support the simultaneous recording and playback of multiple cameras. It comes with an easy-to-install and reliable high-definition solution befitting many Eyenor network products. The recorders are preloaded with all software requirements, including the video management software license. The recorder can be used as a standalone workstation for office environments and a rack server for server rooms. Network Video Recorder supports H.265+, H.265, and H.264 Video formats. It also contains HDMI and VGA simultaneous output. What makes this a smart network video recorder are its face detection options, face and behavior search, and people counting.

4CH EMBEDDED NETWORK VIDEO RECORDER

Model No.	ENR-01004-N-4PK
Appearance	
Type	4CH EMBEDDED NETWORK VIDEO RECORDER
Video Input	4 Ch
Incoming Bandwidth	80 Mbps
Audio Input	1-ch, RCA
HDMI output	3840x2160, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
VGA output	1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Audio output	1-ch, RCA
Outgoing Bandwidth	64 Mbps
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Synchronous Playback	4-ch
Corridor Mode Screen	3/4
VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Abandoned Object, Missing Object
VCA Search	Face Search, Behaviour Search
Statistical Analysis	People counting
USB	Rear panel: 1 x USB2.0, 1 x USB3.0
PoE Interface	4 RJ-45 10M/100M Self Adaptive Ethernet Port
SATA	1 SATA Interface
Array Type	N/A
eSATA	N/A
ANR	Supported
External Storage	N/A
Power Consumption	≤9 W (without HDD)
Dimensions (W×D×H)	260×240×47 mm
Weight (without HDD)	1 Kg

8CH EMBEDDED NETWORK VIDEO RECORDER

Model No.	ENR-01008-N-8PK
Appearance	
Type	8CH EMBEDDED NETWORK VIDEO RECORDER
Video Input	8 Ch
Incoming Bandwidth	64 Mbps
Audio Input	1-ch, RCA
HDMI output	3840x2160, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
VGA output	1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Audio output	1-ch, RCA
Outgoing Bandwidth	48 Mbps
Recording Resolution	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Synchronous Playback	8-ch
Corridor Mode Screen	3/4/5/7/9
VCA Detection	Face detection, Intrusion, Crossing line, Audio detection
VCA Search	Face Search, Behaviour Search
Statistical Analysis	N/A
USB	Rear panel: 2 x USB2.0
PoE Interface	8 RJ-45 10M/100M Self Adaptive Ethernet Port
SATA	1 SATA Interface
Array Type	N/A
eSATA	N/A
ANR	Supported
External Storage	N/A
Power Consumption	≤9 W (without HDD)
Dimensions (W×D×H)	260×240×46 mm
Weight (without HDD)	≤1.1 Kg

16CH EMBEDDED NETWORK VIDEO RECORDER

Model No.	ENR-02016-N-16PK
Appearance	
Type	16CH EMBEDDED NETWORK VIDEO RECORDER
Video Input	16 Ch
Incoming Bandwidth	160 Mbps
Audio Input	1-ch, RCA
HDMI output	3840x2160, 1920X1080, 1920X1080, 1600X1200, 1280X1024, 1280X720, 1024X768
VGA output	1920X1080, 1920X1080, 1280X1024, 1280X720, 1024X768
Audio output	1-ch, RCA
Outgoing Bandwidth	64 Mbps
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Synchronous Playback	16-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16
VCA Detection	Face detection, Intrusion, Crossing line, Audio detection, Defocus detection, Scene change detection, Auto tracking, Abandoned Object, Missing Object
VCA Search	Face Search, Behaviour Search
Statistical Analysis	People Counting
USB	Front panel: 1x USB2.0, Rear panel: 1x USB3.0
PoE Interface	16 RJ-45 10M/100M Self Adaptive Ethernet Port
SATA	2 SATA Interface
Array Type	N/A
eSATA	N/A
ANR	Supported
External Storage	N/A
Power Consumption	≤10W (without HDD)
Dimensions (W×D×H)	380×315×53 mm
Weight (without HDD)	≤2.6 Kg

16CH EMBEDDED NETWORK VIDEO RECORDER

Model No.	ENR-04016-N-16PK
Appearance	
Type	16CH EMBEDDED NETWORK VIDEO RECORDER
Video Input	16 Ch
Incoming Bandwidth	320 Mbps
Audio Input	1-ch, RCA
HDMI/VGA Output	HDMI1/VGA: 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768 HDMI2: 3840x2160, 1920x1080p, 1600x1200, 1280x1024, 1280x720, 1024x768
Audio output	1-ch, RCA
Outgoing Bandwidth	320 Mbps
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Synchronous Playback	16-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16
VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking
VCA Search	Face search, Behavior search
Statistical Analysis	People counting
USB	Front panel: 2 x USB2.0 Rear panel: 1 x USB3.0
PoE Interface	16 RJ-45 10M/100M Self Adaptive Ethernet Port
SATA	4 SATA Interface
Array Type	N/A
eSATA	N/A
ANR	Supported
External Storage	Not Supported
Power Consumption	≤20W (without HDD)
Dimensions (W×D×H)	442×425×89 mm
Weight (without HDD)	≤5.24 Kg

32CH EMBEDDED NETWORK VIDEO RECORDER

Model No.	ENR-04032-N-16PK
Appearance	
Type	32CH EMBEDDED NETWORK VIDEO RECORDER
Video Input	32 Ch
Incoming Bandwidth	320 Mbps
Audio Input	1-ch, RCA
HDMI/VGA Output	HDMI1/VGA: 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768 HDMI2: 3840x2160, 1920x1080p, 1600x1200, 1280x1024, 1280x720, 1024x768
Audio output	1-ch, RCA
Outgoing Bandwidth	320 Mbps
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Synchronous Playback	16-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16/32
VCA Detection	Face detection, Intrusion detection, Line cross detection, Audio detection, Defocus detection, Scene change detection, Auto tracking
VCA Search	Face Search, Behaviour Search
Statistical Analysis	People Counting
USB	Front panel: 1x USB2.0 Rear panel: 1x USB3.0
PoE Interface	16 RJ-45 10M/100M Self Adaptive Ethernet Port
SATA	4 SATA Interface
Array Type	N/A
eSATA	N/A
ANR	Supported
External Storage	Not Supported
Power Consumption	≤20W(without HDD)
Dimensions (W×D×H)	442×425×86 mm
Weight (without HDD)	≤5.24 Kg

32CH EMBEDDED VIDEO NETWORK RECORDER

Model No.	ENR-04032-N-IRK
Appearance	
Type	32CH EMBEDDED VIDEO NETWORK RECORDER
Video Input	32 Ch
Incoming Bandwidth	384 Mbps
Audio Input	1-ch, RCA
HDMI/VGA Output	VGA:1920x1080p, 600x1200, 1280x1024, 1280x720, 1024x768 HDMI1/HDMI2(HDMI audio output is not supported): 3840x2160, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Audio output	1-ch, RCA
Outgoing Bandwidth	384 Mbps
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Synchronous Playback	16-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16/32
VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Abandoned Object, Missing Object
VCA Search	Face Search, Behaviour search
Statistical Analysis	People Counting
USB	Front panel: 2 x USB2.0 Rear panel: 1 x USB3.0
PoE Interface	N/A
SATA	4 SATA Interface
Array Type	RAID 1, 5
eSATA	N/A
ANR	Supported
External Storage	Supported
Power Consumption	≤ 25W (without HDD)
Dimensions (W×D×H)	442×426× 89 mm
Weight (without HDD)	≤ 5.7 Kg

32CH EMBEDDED NETWORK VIDEO RECORDER

Model No.	ENR-08032-N-IRK
Appearance	
Type	32CH EMBEDDED NETWORK VIDEO RECORDER
Video Input	32 CH
Incoming Bandwidth	320Mbps
Audio Input	1-ch, RCA
HDMI/VGA Output	HDMI/VGA: 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768 HDMI2: 3840x2160(4K), 1920x1080p, 1600x1200, 1280x1024, 1280x720, 1024x768
Audio output	1-ch, RCA
Outgoing Bandwidth	320Mbps
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Synchronous Playback	16-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16/32
VCA Detection	Face detection, Intrusion detection, Line cross detection, Audio detection, Defocus detection, Scene change detection, Auto tracking
VCA Search	Face Search, Behaviour search
Statistical Analysis	People Counting
USB	Front panel: 2 x USB2.0 Rear panel: 1 x USB3.0
PoE Interface	N/A
SATA	8 SATA Interface
Array Type	RAID 0, 1, 5, 6, 10
eSATA	Supported
ANR	Supported
External Storage	Supported
Power Consumption	≤ 20 W (without HDD)
Dimensions (W×D×H)	442×425×86 mm
Weight (without HDD)	≤ 5.13 Kg

64CH EMBEDDED NETWORK VIDEO RECORDER

Model No.	ENR-08064-N-IRK
Appearance	
Type	64CH EMBEDDED NETWORK VIDEO RECORDER
Video Input	64 CH
Incoming Bandwidth	384Mbps
Audio Input	1-ch, RCA
HDMI/VGA Output	VGA: 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768 HDMI1/HDMI2 (HDMI audio output is not supported): 3840x2160, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Audio output	1-ch, RCA
Outgoing Bandwidth	384Mbps
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Synchronous Playback	16-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16/32
VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Abandoned Object, Missing Object
VCA Search	Face search, Behavior search
Statistical Analysis	People Counting
USB	Front panel: 2 x USB2.0 Rear panel: 1 x USB3.0
PoE Interface	N/A
SATA	8 SATA Interface
Array Type	RAID 0, 1, 5, 6, 10
eSATA	Supported
ANR	Supported
External Storage	Supported
Power Consumption	≤ 25 W (without HDD)
Dimensions (W×D×H)	442×426×89 mm
Weight (without HDD)	≤ 5.7 Kg



Eyenor ACCESSORIES

Eyenor Camera	Appearance	Part Number & Description
ENV-HVD7M-40R-15 ENC-HCD8F-00R-15 ENV-HD0AF-30R-12 ENC-HCVAM-40R-15		ENH-FDJ6600 Junction Box for Fixed Dome Camera
		ENH-BJ6700 IP66 Rated Square type Junction Box for Eyenor Bullet Camera
		ENB-FDW66 Wall mount bracket for Eyenor Fixed Dome camera
		ENB-ADW66 Incline mount Bracket For Eyenor Fixed Dome Camera
		ENB-DP66 Pole mount Bracket for Eyenor Dome camera
		ENH-WJ0000 NPT 1/4" Plastic Waterproof joint
		ENB-CDP66 220mm Pendant mount bracket for Dome Camera

Eyenor Camera	Appearance	Part Number & Description
ENV-HVD7M-40R-15 ENC-HCD8F-00R-15 ENV-HD0AF-30R-12 ENC-HCVAM-40R-15		ENB-CDP67 520mm Pendant mount bracket for Dome Camera
		ENB-FDP66 Pendant mount bracket for Eyenor Fixed Dome Camera
		ENB-UV66 Vertical Pole mount Bracket for Eyenor Bullet camera
ENV-HCBAF-30R-12		ENH-CBJ6600 IP66 Rated Circular type Junction Box for Eyenor Compact Bullet Camera
		ENB-UV65 Vertical Pole mount Bracket for Eyenor Bullet camera
		ENH-WJ0000 NPT 1/4" Plastic Waterproof joint

Eyenor Camera	Appearance	Part Number & Description
ENC-HHP8Z-50R-11		ENH-BJ6700 IP66 Rated Square type Junction Box for Eyenor Bullet Camera
		ENB-UV66 Vertical Pole mount Bracket for Eyenor Bullet camera
		ENB-UV65 Vertical Pole mount Bracket for Eyenor Bullet camera
		ENH-WJ0000 NPT 1/4\"
		ENH-CDJ6500 Junction Box for 5MP Turret Dome Camera
		ENH-WJ0000 NPT 1/4\"
		ENB-CDP66 220mm Pendant mount bracket for Dome Camera

Eyenor Camera	Appearance	Part Number & Description
		ENB-CDP67 520mm Pendant mount bracket for Dome Camera
		ENB-FDP66 Pendant mount bracket for Eyenor Fixed Dome Camera
ENC-HC85F-30R-15		ENH-BJ6601 IP66 Rated Square type Junction Box for Eyenor Bullet Camera
		ENH-BJ6600 IP66 Rated Circular type Junction Box for Eyenor Bullet Camera
		ENB-UV65 Vertical Pole mount Bracket for Eyenor Bullet camera
		ENH-WJ0000 NPT 1/4\"

Eyenor Camera	Appearance	Part Number & Description
ENC-HHP5Z-250R-14		ENB-PPAC Pendent mount adaptor for ceiling mount
		ENB-CP66 Ceiling mount Bracket for Eyenor PTZ Camera
		ENB-PP66 Pendent mount Bracket for Eyenor PTZ Camera
		ENB-OP67 Pendant Mount bracket for Eyenor Dome Camera
		ENH-PJ6600 IP66 Rated Junction Box for Eyenor PTZ Camera
		ENB-PW67 Wall mount Bracket for Eyenor PTZ Dome Camera
		ENB-GPW66 Gooseneck Bracket mount for Eyenor PTZ Dome Camera

Eyenor Camera	Appearance	Part Number & Description
ENC-HHP5Z-250R-14		ENB-PV66 Vertical Pole mount Bracket for Eyenor PTZ Camera
		ENB-PH66 Corner mount Bracket for Eyenor PTZ Dome Camera

An aerial photograph of a city, likely New York City, with a green tint. Overlaid on the image are several white security-related icons: shields with keyholes, shields with crosshairs, and circular arrows. Thin white lines connect these icons to various points on the cityscape, suggesting a network or monitoring system.

Our SOFTWARE

Eyenor software range supports and supplements a spectrum of applications for mobiles and PCs. It allows end-users, monitoring stations, and installers to have remote controls to their systems. Thus, accurate responses are made to the alarms generated at any given time.

THE APPLICATIONS



Eyenor Video Management Software (VMS) (Windows and Mac)

Recording Management, playback, PT Control, Alarm, E-Map, Live View and Video Wall



Eyenor VMS (iOS, Android)

Helps in viewing live or recorded footage, receives alarms, and manages cloud devices using mobiles.



Eyenor Tool

It is a tool kit used for upgradation, device search, capacity calculations, remote configuration, and time recording



Eyenor Analytics

Motion detection, face recognition, people counting, scene changes, tampering alarm etc.



The Norden Partner PROGRAM

The Norden Partner Program is a business partnership strategy that assists our channel partners to provide Norden products and services in the knowledge that they have the full support of a Global organization. Our Channel Partners are fully trained and able to install Norden products. Accredited Partners include value-added resellers (VARs), system integrators (SI), and distributors.

HOW DOES THE NORDEN PARTNER PROGRAM WORK?

Norden Channel Partners benefit from technical and marketing resources in return for the active promotion of the range of solutions. The typical benefits to the partner are:

TECHNICAL TRAINING AND SALES ENABLEMENT.

Norden will provide technical training in various formats, such as online courses via learning management systems or in-person sessions. Sales enablement content can include white papers, sales scripts, competitor comparisons and presentations – all of which is aimed at preparing a partner's sales teams for customer engagements. Discounted NFR demo kit will also be available.

INCENTIVES AND DISCOUNTS.

Partners will be incentivized to resell Norden products and services. Rewards can include enhanced discounts, back-end rebates and sales performance incentive funds.

PROJECT REGISTRATION.

Partners use the Norden Project Registration System to register projects and request exclusive rights for pursuing the deal. Project registration helps partners protect their investment in sales opportunities. Norden will offer exclusive assistance to the registered partner to assist in the winning of the project.

MARKETING ASSETS.

The Norden Partner Program will generally offer a range of marketing materials, tools and resources that partners can use to launch campaigns.

PARTNER PORTALS.

Using the portal, partners can access Norden's project registration system, online training, and sales and marketing information and content.

TIERS OF PARTNER.

The Norden Partner Program will recognise training and commitment levels from the Partner and offer additional incentives in return. It will be relevant to specific product family; NCS, Secnor, Eyenor & NVS. The levels will be Certified, Approved and Advanced.



Partner DEFINITIONS

DISTRIBUTOR – (NDP) NORDEN DISTRIBUTION PARTNER

Support channel, gain tractions from installer base, sales support, hold stock

TECHNOLOGY PARTNER – (NTP) NORDEN TECHNOLOGY PARTNER

Offer value add solutions to increase the technology value of the solution

ADVANCED INTEGRATOR – (NAP) NORDEN ADVANCED INTEGRATION PARTNER

Highest technical training levels across all Norden triangle products

APPROVED INSTALLER – (*AI) *APPROVED INSTALLER

Fully trained in an individual part of the Norden triangle range

CERTIFIED INSTALLER – (*CI) *CERTIFIED INSTALLER

Fully trained in an individual part of the Norden triangle range

Talk To US



► **NORDEN®** GLOBAL PRESENCE

To know more or book demonstration about our products, do not hesitate to contact us. We will be more than delighted to support you!

NORDEN COMMUNICATION UK LTD.,

Unit 13 Baker Close
Oakwood Business Park
Clacton on Sea
Essex CO15 4BD
United Kingdom

Tel : +44 (0)1255 474063

E-mail : salesuk@norden.co.uk

EYENOR[®]

